

INFINITY

Dry Brite Floor Finish/High Gloss/
Hard Surface Protection

SPECIAL FEATURES

The perfect fit for facilities that require non-burnishing maintenance systems, radiant off the mop gloss and a high level of durability. Infinity, Dry/Brite floor finish is highly effective for low-to-medium traffic areas such as patient rooms, classrooms and offices. Infinity shines with outstanding off the mop gloss and sustains great levels of durability while drying quickly for minimum facility down time. Infinity prides itself on its ease of maintenance, application, repairability, and outstanding film clarity.

DIRECTIONS

For best results, strip floors with PS Infinity Stripper, neutralize and clear water rinse. Check pH of floor to ensure it is neutral. For porous floors, new floors, or high traffic areas apply 4-5 coats of PS Infinity. For non-porous floors, simply apply 4 coats of PS Infinity Floor finish. For re-coating, clean floor thoroughly with PS Floor Cleaner, rinse and apply 1 to 3 coats of PS Infinity floor finish. Burnishing is not required. Restore with regular cleaning use of PS Floor Cleaner.

STRIP, NEUTRALIZE, RINSE, 4-5 INFINITY COATS

Manufactured by:
Ultra Chem Labs Corp.
www.ultrachemlabs.com
Tel-909-605-1640
Fax-909-605-1068
4581 Brickell Privado St
Ontario, CA 91761

Properties

Appearance: Milky white
Finish Type: Acrylic
Polymer (Super Durable)
VOC's: 4 gm/L
Solid Content: 27%
pH: 8.5
Weight/Gallon: 10 lb
Coverage:
1500-2500 sq. ft./gallon
Soil Resistance: Excellent
Drying Time: 15-45 minutes
(depending on humidity)
Color of Dry Film: Water Clear
Application Temperature:
50 degrees F (Minimum)
Storage Temperature:
40 degrees F - 85 degrees F
Storage Stability:
1 year under normal conditions
Freeze Thaw Stability:
Passes one cycle

INFINITY exceeds Slip
Resistance standards when
tested according to ASTM
D3052-87: 0.5
(Slip Resistant)