

Sealer

High Performance/Durable
Fortifying Protection for Hard Surfaces

SPECIAL FEATURES

Sealer is a high performance easy to apply acrylic floor sealer. Sealer is best used to seal/protect extremely porous and worn out floors before applying Infinity floor finish to most floor surfaces. Sealer dries very quickly to avoid any facility downtime. As a result, Sealer will have your floors primed for the best protective condition in very quick fashion.

DIRECTIONS

- For best results, strip floors with PS Infinity Stripper, neutralize and clear water rinse. Check pH of floor to ensure it is neutral.
- For porous floors, new floors, or high traffic areas apply 2 coats of PS Infinity Floor Sealer.

STRIP, NEUTRALIZE, RINSE, APPLY 2 COATS OF SEALER

Manufactured by:
Ultra Chem Labs Corp.
www.ultrachemlabs.com
Tel-909-605-1640
Fax-909-605-1068
4581 Brickell Privado St
Ontario, CA 91761

Properties

Appearance: Milky white
Finish Type: Acrylic Polymer
VOC's: 4 gm/L
Solid Content: 16%
pH: 8.5
Weight/Gallon: 10 lb
Coverage:
800-1200 sq. ft./gallon
Soil Resistance: Excellent
Drying Time: 15-45 minutes
(depending on humidity)
Color of Dry Film: Water Clear
Application Temperature:
50 degrees F (Minimum)
Storage Temperature:
40 degrees F - 85 degrees F
Storage Stability:
1 year under normal conditions
Freeze Thaw Stability:
Passes one cycle

Sealer exceeds Slip Resistance standards when tested according to ASTM D3052-87: 0.5 (Slip Resistant)